

CONVERTEX

SCHEMA TECNICA 30.6.2023

SILCOT**FABRIC IDENTIFICATION : SINGLE JERSEY WITH DOUBLE ENZYME ANTIPILLING TREATMENT - NC 6004 1000****KNITTING 2023**

Diameter 34

Gauges – Finezza :28

YARN TECHNICAL DATA

Composition : 94% COTTON 6% ELASTANE

Count of yarn – Titolo fibra

Ne

30/1 COMP.COMBED

FABRIC TECHNICAL DATA

Cert. Oeko-Tex Standard 100: No

RAW

FINISHED

Parameter

U.M.

Value

tolerance +/-

Value

tolerance +/-

Overall width (min) - altezza cm

cm.

205

180

% 5

Weight / sq. metre - Peso g/mq

g.

185

220

% 5

FABRIC SHRINKAGE – RITIRO DEL TESSUTO

Shrinkage:

U.M.

LENGHT

toler. +/-

WIDTH

toler. +/-

Washing - lavaggio

%

-5

2%

-5

2%

Turning – in arrotolamento

%

1

Spirality 5%

WASHING FASTNESS 3-4

LIGHT FASTNESS 3-4

PILLING 3-4

Take note of the tolerances also in composition

Washing

Wash gently in the machine. Water temperature 40 C

**Bleaching**

Dont use Bleaching agent

**Drying**

Dont Dry it in the thumble machine. Dry it as hang dry or line dry

**Ironing**

Iron it with low temperature

**Dry Cleaning**

Except Tricloretilen dont use any Dry Cleaning Agent

